

TWO-COMPONENT FOAM PRO TIPS:

1. CHOICE OF KIT TYPE

Standard two-component kits are perfect for coverage applications as an insulator and air sealant. Class 1 rated two-component foam is recommended for rim-joint sealing applications (foam plastic spray applied to a sill plate and header of Type V construction), where flame retardant requirements specify the use of an E-84 Class 1 rated foam. (Refer to I.R.C., Chapter 26, Plastic, Section 2603.4 and Section 2603.4.1.11 for exact code requirements.)

2. CHOICE OF KIT SIZE

All two-component kits provide theoretical yield measured in “board foot.” This is a measurement of foam sprayed 1" thick over a specific square footage of application surface, i.e., a 200 board foot kit will cover a 200 square foot area with foam applied 1" thick. Actual yield may vary depending on the ambient conditions and particular application.

3. PERSONAL PROTECTION

Always wear protective eyewear, impervious gloves and appropriate work clothing protection (Tyvek suit) when applying two-component foam. Use only with adequate ventilation or certified respiratory equipment.

4. PREPARATION

Make sure that the work area is clean of any debris or items that could potentially interrupt or slow down the application once you have started applying the foam. Two-component foam begins curing as quickly as the foam is expelled from the nozzle tip and can potentially clog the tip if spraying is suspended for 30 seconds or longer. Spare spray tips are provided with each kit.

Technical Data Sheets, Operating Instructions and MSDS Sheets are readily available for both Dow Froth-Pak and Fomo Handi-Foam. Please call or email your sales rep to request a copy or download the information at www.adodistribution.com. Operating Instructions are provided within each kit.

Each installer is responsible to carefully read and maintain the Technical Data Sheets, Operating Instructions and MSDS Sheets to insure proper safety, handling and installation takes place. Consult your local building codes for specific requirements.

